



DOWCAL N

Inhibited Propylene Glycol-based Heat Transfer Fluid

DOWCAL* N heat transfer fluid is a propylene glycol-based fluid that is low in acute oral toxicity and widely used to depress freeze points in food and beverage processing and in other applications. Available only in Europe, it features a specially formulated corrosion inhibitor package.

Key Features of DOWCAL N Fluid:

- Better freeze protection
- Better corrosion protection in hot and cold systems
- FDA approved safe food additive
- Compatible with commonly used elastomers
- Long fluid life and low maintenance costs
- Greater cost-effectiveness
- Low acute oral toxicity

Recommended use temperature

range: -45°C (-50°F) to 120°C (250°F)

Typical Freezing and Boiling Points of DOWCAL N Fluid†

Wt. % Propylene Glycol	Vol. % Propylene Glycol	Wt. % DOWCAL N	Vol. % DOWCAL N	Freezing Point °C (°F)	Boiling Point °C @ 1.013 bar (°F @ 760 mmHg)	Refractive Index 20°C (68°F)
0.0	0.0	0.0	0.0	0 (32.0)	100 (212)	1.333
5.0	4.8	5.2	5.0	-2 (29.1)	100 (212)	1.339
10.0	9.6	10.5	10.1	-3 (26.1)	100 (212)	1.344
15.0	14.5	15.7	15.2	-5 (22.9)	100 (212)	1.350
20.0	19.4	20.9	20.3	-7 (19.2)	101 (213)	1.356
25.0	24.4	26.2	25.5	-10 (14.7)	101 (214)	1.364
30.0	29.4	31.4	30.8	-13 (9.2)	102 (216)	1.369
35.0	34.5	36.6	36.1	-16 (2.4)	103 (217)	1.375
40.0	39.6	41.9	41.5	-21 (-6.0)	104 (219)	1.380
45.0	44.7	47.1	46.8	-27 (-16.1)	104 (220)	1.386
50.0	49.9	52.4	52.3	-34 (-28.3)	106 (222)	1.392
55.0	55.0	57.6	57.6	-42 (-42.8)	106 (223)	1.397
60.0	60.0	62.8	62.8	-51 (-59.9)	107 (225)	1.402
65.0	65.0	68.1	68.1	a	108 (227)	1.407
70.0	70.0	73.3	73.3	a	110 (230)	1.411
75.0	75.0	78.5	78.5	a	114 (237)	1.416
80.0	80.0	83.8	83.8	a	119 (245)	1.420
85.0	85.0	89.0	89.0	a	128 (257)	1.424
90.0	90.0	94.2	94.2	a	138 (270)	1.428
95.5	95.5	100.0	100.0	a	167 (310)	1.432

†Typical properties, not to be construed as specifications.

*Freezing points are below -50°C (-60°F).

NOTE: Generally, for an extended margin of protection, you should select a temperature in this table that is at least 3°C (5°F) lower than the expected lowest ambient temperature. Inhibitor levels should be adjusted for solutions of less than 30% glycol. Contact Dow for information on specific cases or further assistance.

*Trademark of The Dow Chemical Company

DOWCAL N Inhibited Propylene Glycol-based Heat Transfer Fluid

Typical Properties of DOWCAL N Fluid[†]

DOWCAL N Heat Transfer Fluid	
Composition (% by weight)	
Propylene Glycol	96
Inhibitors & Water	4
Color	Pale Yellow
Specific Gravity	
15/15°C (60/60°F)	1.050–1.060
pH of Solution	
(50% glycol)	9.0–10.0
Reserve Alkalinity (min.)	10.0 ml

[†]Typical properties, not to be construed as specifications.
Complete sales specifications are available on request.

Saturation Properties of DOWCAL N Fluid at 30% Propylene Glycol Concentration by Volume

Temp. °C (°F)	Specific Heat kJ/(kg) (K)	Density kg/m ³	Thermal Conductivity W/mK	Viscosity mPa·s
0 (32)	3.81	1,036	0.428	6.43
25 (77)	3.88	1,026	0.456	2.43
50 (122)	3.95	1,013	0.476	2.22
75 (167)	4.01	996	0.489	0.74
100 (212)	4.08	977	0.493	0.51
120 (248)	4.13	959	0.492	0.41

Saturation Properties of DOWCAL N Fluid at 40% Propylene Glycol Concentration by Volume

Temp. °C (°F)	Specific Heat kJ/(kg) (K)	Density kg/m ³	Thermal Conductivity W/mK	Viscosity mPa·s
0 (32)	3.67	1,045	0.391	11.40
25 (77)	3.75	1,034	0.413	3.51
50 (122)	3.83	1,019	0.429	1.59
75 (167)	3.91	1,002	0.438	0.92
100 (212)	3.99	981	0.441	0.62
120 (248)	4.05	962	0.439	0.49

Saturation Properties of DOWCAL N Fluid at 50% Propylene Glycol Concentration by Volume

Temp. °C (°F)	Specific Heat kJ/(kg) (K)	Density kg/m ³	Thermal Conductivity W/mK	Viscosity mPa·s
0 (32)	3.50	1,052	0.357	16.33
25 (77)	3.59	1,040	0.374	4.93
50 (122)	3.69	1,024	0.385	2.14
75 (167)	3.78	1,005	0.392	1.18
100 (212)	3.87	984	0.393	0.76
120 (248)	3.95	964	0.390	0.58

For further information, call...

In The United States And Canada: 1-800-447-4369 • Fax: 1-517-832-1465

In Europe: +31 20691 6268 • Fax: +31 20691 6418

In The Pacific: +886 22 547 8731 • Fax: +886 22 713 0092

In Other Global Areas: 1-517-832-1556 • Fax: 1-517-832-1465

<http://www.dow.com/heattrans>

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Published April 1998

